



Non-linear broad spectral tuning of a semiconductor laser and application to coherent dual frequency source

Baptiste Chomet, Stéphane Blin, Adrian Bartolo, Grégoire Beaudoin, Isabelle Sagnes, Arnaud Garnache

► To cite this version:

Baptiste Chomet, Stéphane Blin, Adrian Bartolo, Grégoire Beaudoin, Isabelle Sagnes, et al.. Non-linear broad spectral tuning of a semiconductor laser and application to coherent dual frequency source. Conference on Lasers and Electro-Optics/Europe (CLEO/Europe 2023) and European Quantum Electronics Conference (EQEC 2023), Jun 2023, Munich (Allemagne), Germany. pp.cb_10_6, 10.1109/CLEO/Europe-EQEC57999.2023.10231833 . hal-04283051

HAL Id: hal-04283051

<https://hal.umontpellier.fr/hal-04283051>

Submitted on 13 Nov 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Non-linear broad spectral tuning of a semiconductor laser and application to coherent dual frequency source

B. Chomet¹, S. Blin², A. Bartolo², G. Beaudoin³, I. Sagnes³ and A. Garnache²

1. Laboratoire de Physique de l'École Normale Supérieure, 75005 Paris, France

2. IES, Univ Montpellier, CNRS, Montpellier, France

3. C2N, CNRS UMR 9001, Université Paris-Saclay, 91120 Palaiseau, France

Laser technology is finding applications in areas such as high-resolution spectroscopy, radar-lidar, velocimetry, or atomic clock where highly-coherent tunable high-power light sources are required. Offering such performances in the Near- and Middle-IR range, III-V semiconductor-based Vertical-external-Cavity Surface-Emitting Lasers (VeCSEL) technologies seem to be a well-suited path to meet the required specifications of demanding applications [1].

As an example, we demonstrate that a dual-frequency VeCSEL based on the coexistence of two Laguerre-Gauss (LG) transverse modes was suitable to provide coherent and tunable THz emission using photomixing techniques [2], the coherence being verified in terms of longitudinal modes, transverse modes and polarization (linear state). The typical optically-pumped laser structure is shown in Fig. 1a, and the resulting output beam that consists of the superimposition of LG_{00} and LG_{03} modes is shown in Fig. 1b. In this two-modes laser, the frequency difference between the two transverse modes could be tuned by the optical pump power from 50 GHz to about 900 GHz, but this outstanding tuning range could not be solely explained by linear thermal effects ruled by the pump beam. Therefore, a fundamental study of the non-linear multimode laser dynamics was carried out to explore phase-amplitude dynamic instabilities [3], by taking into account combined key physical effects such as cavity dispersion and diffusion, four-wave mixing and light-matter-interaction-induced phase-amplitude coupling.




Fig. 1 **a)** Diode-pumped VeCSEL device design. **b)** Transverse modes (LG_{00} & LG_{03}) superimposition observed at the laser output. **c)** Non-linear broad spectral tuning map as a function of intracavity pump power for dual-mode operation involving LG_{00} & LG_{03} transverse modes, the LG_{00} mode operates at the higher wavelength.

We report experimentally and theoretically the existence of deterministic dynamics of the laser field, with a route to robust single-frequency operation exhibiting broad non-linear spectral tuning far above the thermally-assisted conventional tuning range [3]. This study provides physical explanations for the beat-frequency shift observed in the dual-frequency VeCSEL as shown in Fig. 1c, with a linear shift driven by thermal effects at low pump power (< 275 mW), and a non-linear shift at higher pump power characterized by a low intracavity bifurcation threshold intensity of typically 10's kW/cm². These results pave the way to frequency-tuning management in such coherent lasers, either for robust single-frequency operation or dual-frequency operation.

This work was supported by ANR SPATIOTERA program (grant number ANR-19-CE24), ANR BLASON (grant number ANR-18-CE24-0002), I-SITE MUSE AAP2021 (STAE), and C2N RENATECH network.

References

- [1] A. Laurain et al., "Multiwatt-power highly-coherent compact single-frequency tunable Vertical-External-Cavity-Surface-Emitting-Semiconductor-Laser," *Opt. Express* **18**, 14627 (2010).
- [2] S. Blin et al., "Coherent and tunable THz emission driven by an integrated III-V semiconductor laser," *IEEE J. Sel. Topics Quantum Electron.* **23**, 1500511 (2017).
- [3] B. Chomet in, *Integration of high coherence tunable semiconductor laser. Non linear multimode dynamics and route to single frequency operation*, Ph.D. thesis (Univ. Montpellier, 2019).